

PINCH VALVE SLEEVE MODEL SELECTION GUIDE

SBRT 10/100/250/3LC2

SBRT	SLEEVE SPECIALITY	10 PRESSURE CLASS (PN)	100 VALVE SIZE (mm)	250 SLEEVE LENGTH (mm)	3 SHAPE OF FLANGE	L OPENING TAGS	C CONICALITY**	2 FLANGE DRILLING****
SBRT = Styrene butadiene EPDM = Ethylene propylene NR = Natural rubber NBR = Nitrile CSM = Hypalon EPDMB = Green liquor sleeve CR = Chloroprene IIR = Butyl NRF = Foodstuff natural rubber NBRF = Foodstuff nitrile HNBR = Hydrogenated nitrile FPM = Fluorine rubber	/M = Flowrox SensoMate sleeve a) /PU = PU-Lining inside the sleeve /VAC = SUCTION sleeve /VAC/M = Suction sleeve with Flowrox SensoMate sleeve /VAC/PU = Suction sleeve with PU-coating inside the sleeve /ETPU = Extra thick PU-Lining inside the sleeve*	1 = 1 bar 6 = 6 bar 10 = 10 bar 16 = 16 bar 25 = 25 bar 40 = 40 bar 64 = 64 bar 100 = 100 bar	25.....1000 25-10** 150(100)*	Determined by the valve Flowrox (depending on the valve diameter /pressure class)	1 3 2*** 4	L	C S CU Determined by the valve Flowrox (depending on the valve diameter /pressure class)	2 = DIN PN 10 3 = DIN PN 16 4 = DIN PN 25 5 = DIN PN 40 6 = ANSI 150 7 = ANSI 300 8 = BS TABLE D 9A = AS TABLE D 9B = AS TABLE E 9C = JIS 10K 9D = JIS 16K 9 = OTHER
SLEEVE MATERIAL		PRESSURE IN BAR		LENGTH OF THE SLEEVE		OPENING TAGS		
SPECIAL COATING/FEATURES		VALVE SIZE		FLANGE TYPE				

**USED FOR CONICAL SLEEVES ONLY: C: EVEN CONICALITY (OUTER DIAMETER), CU: UNVEVEN CONICALITY (OUTER DIAMETER) S: STRAIGHT OUTER DIAMETER (BIGGER DN-SMALLER DN)

*EXTRA THICK PU-LINE, REDUCED BORE, PN RATED 1 BAR ONLY, SIZE MARKING: VALVE DN(PIPE DN) EX. 150(100)

*** SOLD AS SPARES ONLY

****USE WHEN ORDERING, FOR FLANGE TYPE 3.

a) NOT AVAILABLE FOR CONICAL SLEEVES.

